

# PJD7382

## ULTRA-SHORT THROW PROJECTOR

120HZ AND 3D-READY

### Small budget-big presentations.

The powerful PJD7382 120Hz 3D-ready projector combines powerful features with RJ45 network capability. The projector offers an extreme short throw ratio – producing a large 81-inch image at a distance of only 39 inches away. With its short throw lens, the PJD7382 saves space by allowing you to place it at the front of your table and still display large, crisp images. With 3,000 lumens and a 3000:1 contrast ratio, your images look great in a classroom, boardroom or virtually any setting. All these features are packed into an attractive, compact design weighing only 7.7 lb. Multiple preset presentation modes, an increased 40 degree digital vertical keystone correction and digital zoom ensure the best possible image regardless of location. Choose the PJD7382 for up to 6,000 hours of lamp life\*, low cost replacement lamps, filter-free design and a non-degrading DLP® light engine for the best warranty and low total cost of ownership.



### VERSATILE PRESENTATION ANYWHERE

- > **Short throw lens for large, stunning images in small places**  
The short throw lens enables large images to be projected from short distances in small rooms with short throw distances. A screen size of 81-inch is possible from just 39 inches.
  - > **BrilliantColor™ technology**  
Latest BrilliantColor technology delivers stunning all-digital clarity with life-like color, sharp graphics and outstanding video. The sophisticated 6-segment color wheel enhances the yellow color performance that is key to accurate and vivid color reproduction.
  - > **Bright in virtually any setting with 3,000 lumens**  
Packs 3,000 ANSI lumens in just 7.7 pounds, and with a high 3000:1 contrast ratio (typ), your presentations are guaranteed to be vibrant even in the brightest office environment.
  - > **Network control through RJ45**  
Schedule, manage and monitor the projector remotely and receive e-mail alerts of projector lamp status. Use the unique integrated clock to perform commands even when the host PC is powered down.
  - > **Eco-mode extends lamp life**  
Extend the life of your lamp up to 6,000 hours and reduce noise output.
  - > **Off-to-Go feature**  
This feature allows the busy presenter to simply unplug the projector and go without waiting for the usual cool down phase. This feature also protects lamp life from sudden power blackout.
- > **Supports Crestron RoomView® Express**  
Manage up to 250 network projectors in real time monitoring and control. Manage assets, schedule events and program email alerts with this amazing software.



VIEWSONIC  
PRODUCTS, PROGRAMS,  
AND SERVICES

**ViewSonic®**  
See the difference® 

# PJD7382

## ULTRA-SHORT THROW PROJECTOR – 120HZ AND 3D-READY



### Optional Accessories

- > Replacement Lamp RLC-057
- > Short throw mount WMK-027
- > Wireless G Presentation Gateway WPG-350
- > Extended Express Exchange® PRJ-EE-08-03

Projection Distance		4:3 Screen Size	
M	Feet	M	Inches
0.5	1.6	1.0	40
1.0	3.3	2.0	80
1.2	3.9	2.5	100
1.5	4.9	3.0	120
2.5	8.2	5.1	200
3.7	12.1	7.6	300

<b>DISPLAY</b>	Type	0.55" Digital Micromirror Device (DLP™)
	Resolution	XGA 1024x768 (Native) / UXGA 1600x1200 (compressed)
	Lens	Fixed Lens / Digital Zoom / Manual Focus
	Keystone	Vertical digital keystone correction: +/- 40 degrees
	Display Size (Diagonal)	30"–300" / .762m–7.62m
	Throw Distance	0.5m–3.7m / 1.6ft–12.1ft
	Throw Ratio	0.61:1
	Lamp	210 watt
	Lamp Life (Normal / Eco-mode)	4000 / 6000 hours
	Brightness	3000 Lumens
	Contrast Ratio	2600:1 static (typ); 3000:1 (dynamic)
	Aspect Ratio	4:3 (native) and 16:9
Color Depth	24 bits, 16.7M color (8+8+8)	
Color Wheel	6-Segment RGBCYW / 7200rpm	
Color Gamut	90% NTSC 1931 CIE	
<b>INPUT SIGNAL</b>	Computer and Video	NTSC M (3.58 MHz), 4.43MHz, PAL (B, D, G, H, I, M, N, 60), SECAM, SD 480i and 576i (24fps, 25fps and 30fps), ED 480p and 576p (24fps, 25fps and 30fps), HD 720p, 1080i (24fps, 25fps and 30fps)
	Frequency	F <sub>H</sub> : 31–100KHz, F <sub>V</sub> : 48–120Hz
<b>COMPATIBILITY</b>	PC	VGA to UXGA
	Mac®	Up to 1024x768 (may require Mac adapter)
<b>CONNECTOR</b>	RGB Input	15-pin mini D-sub (x2)
	RGB Output	15-pin mini D-sub
	Composite Input	RCA jack
	S-video Input	4-pin mini-DIN
	Audio Input	3.5mm mini jack (x1), RCA (L/R)x1
	Audio Output	3.5mm mini jack
	Mic-In	3.5mm mini jack
	12V trigger	3.5mm/1A
	Control	RS-232 (9-pin mini-DIN)/RJ-45
	<b>AUDIO</b>	Speaker
<b>POWER</b>	Voltage	100~240VAC (Auto Switching), 50/60Hz (universal)
	Consumption	296W (typ) / 1W (stand-by mode)
<b>CONTROLS</b>	Basic	Power, keystone/arrow keys, left/blank, menu/exit, right/panel key lock, auto, mode/enter, source
	OSD	<b>Picture:</b> Brightest, contrast, color setting, keystone, aspect ratio, image, white intensity, gamma, 3D sync, 3D sync invert <b>Computer Image Picture:</b> Brightest, contrast, color setting, keystone, aspect ratio, image, white intensity, gamma, 3D sync, 3D sync invert <b>Computer Image:</b> Frequency, tracking, H position, V position <b>Video Image:</b> Saturation, sharpness, tint <b>Setting:</b> Menu position, projection, signal type, lamp hour, lamp hour reset, filter mode, filter hours, filter hours reset, power saving, auto source, Eco-mode, high altitude, OSD timeout
<b>OPERATING CONDITIONS</b>	Temperature	32°F–104°F (0°C–40°C)
	Humidity	10%–90% (non-condensing)
	Altitude	0~6,000 ft. (1,800m), operational up to 10,000 ft. (3048m)
<b>NOISE LEVEL</b>	Normal / Eco-mode	32dB / 27dB
	<b>DIMENSIONS (W x H x D)</b>	Physical 11.4" x 5.0" x 10.0" / 290mm x 126mm x 254mm Packaging 15.0" x 8.3" x 15.4" / 380mm x 210mm x 392mm
<b>WEIGHT</b>	Net	3.5 lb. (7.7 kg)
	Gross	12.1 lb. (5.5 kg)
<b>REGULATIONS</b>	CB, RoHS, WEEE, UL/cUL, FCC-B, ICES-003, IRAM (Argentina), NOM, PSB, C-tick, EK, CE, TUV/GS, GOST-R, Hygienic, SASO UKrSEPRO, CCC	
<b>PACKAGE CONTENTS</b>	ViewSonic projector, power cable, VGA cable, laser remote control with batteries, lens cap, Quick Start Guide, ViewSonic Wizard CD (with User Guide)	
<b>WARRANTY</b>	3-year limited warranty on parts and labor, 1-year limited warranty on lamp, 1st year Express Exchange® service**	



ViewSonic Corporation's OMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by TUV NORD.

Sales: (888) 881-8781 . SalesInfo@ViewSonic.com . ViewSonic.com

\*Running eco-mode exclusively can extend lamp life. \*\*See ViewSonic.com for full Express Exchange details. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2010 ViewSonic Corporation. All rights reserved [15038-01B-06/10] PJD7382-1

**ViewSonic®**  
See the difference®

For more product information, visit us on the web at ViewSonic.com